

Ranger Pro Gateway Warning, Special Conditions and Additional Information

Safety Note

Bently Nevada Machinery Condition Monitoring

158M1429 Rev. -



Copyright 2021 Baker Hughes Company. All rights reserved.



Bently Nevada, Ranger and Orbit Logo are registered trademarks of Bently Nevada, a Baker Hughes Business, in the United States and other countries. The Baker Hughes logo is a trademark of Baker Hughes Company. All other product and company names are trademarks of their respective holders. Use of the trademarks does not imply any affiliation with or endorsement by the respective holders.

Baker Hughes provides this information on an "as is" basis for general information purposes. Baker Hughes does not make any representation as to the accuracy or completeness of the information and makes no warranties of any kind, specific, implied or oral, to the fullest extent permissible by law, including those of merchantability and fitness for a particular purpose or use. Baker Hughes hereby disclaims any and all liability for any direct, indirect, consequential or special damages, claims for lost profits, or third party claims arising from the use of the information, whether a claim is asserted in contract, tort, or otherwise. Baker Hughes reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your Baker Hughes representative for the most current information.

The information contained in this document is the property of Baker Hughes and its affiliates; and is subject to change without prior notice. It is being supplied as a service to our customers and may not be altered or its content repackaged without the express written consent of Baker Hughes. This product or associated products may be covered by one or more patents. See [Bentley.com/legal](https://www.bentley.com/legal).

1631 Bently Parkway South, Minden, Nevada USA 89423
Phone: 1.775.782.3611 (US) or [Bentley.com/support](https://www.bentley.com/support)
[Bentley.com](https://www.bentley.com)

Contents

1.1 Purpose	4
1.2 Conditions of Safe Use	4
1.3 Additional Warnings	4
1.4 Avertissements supplémentaires	5
1.5 Environmental Ratings	5
1.6 Electrical Ratings	6
1.7 Approved Battery	6
1.8 Hazardous Location Certification Markings	6

1.1 Purpose

This document conveys the warnings, special conditions, and additional information for the safe use of the Ranger Pro Gateway operated in hazardous locations.

Refer to Ranger Pro Gateway User Guide document (158M1430) for general instructions and additional information.



1.2 Conditions of Safe Use

The following conditions of safe use apply:

- The Power over Ethernet function may not be utilized in a hazardous atmosphere. Only a suitable DC power supply may be utilized to power the equipment in a hazardous area.
- For outdoor installation, the connector guard must be installed to protect against UV exposure.

1.3 Additional Warnings

The following warnings apply in addition to any marking on the equipment.

	WARNING
	POTENTIAL ELECTROSTATIC CHARGING HAZARD The equipment shall only be cleaned with a damp cloth when deployed in a hazardous area.

	WARNING
	DO NOT CONNECT OR DISCONNECT WHEN ENERGIZED.

1.4 Avertissements supplémentaires

Les avertissements suivants doivent être appliqué en complément des autres instructions indiquées sur l'équipement.



1.5 Environmental Ratings

Operating Environment	Indoor or Outdoor use. Dry or Wet locations.
Temperature	-40°C ≤ Ta ≤ +70°C
Ingress Protection	IP66/67
Enclosure Type	Type 4X
Relative Humidity	5 to 95 % (noncondensing)
Altitude	≤ 3000m
Pollution Degree	4

1.6 Electrical Ratings



Rated Voltage	20-57 Vdc
Rated Power	≤ 4W
Overvoltage	Overvoltage Category II

1.7 Approved Battery

Only use the Murata CR2032X 220mAH Manganese Dioxide Lithium Coin Battery approved for use with the equipment. The use of any other battery or cell will void the safety rating and present a significant safety hazard.

1.8 Hazardous Location Certification Markings

The Ranger Pro Gateway has been tested and certified for the following markings as applicable:

North America (US and Canada)	Ex ec IIC T4 Gc Ex tc IIIC T135°C Dc Class I, Zone 2, AEx ec IIC T4 Gc Zone 22, AEx tc IIIB T135°C Dc Class I, Div. 2, Grp ABCD T4 Class II, Div. 2, Grp FG T135°C -40°C ≤ Ta ≤ +70°C
IECEX	Ex ec IIC T4 Gc Ex tc IIIC T135°C Dc -40°C ≤ Ta ≤ +70°C IECEX ICS 21.0015X
ATEX (EU)	<div style="display: flex; align-items: center;"> <div style="margin-right: 20px;">  </div> <div style="margin-right: 20px;"> II 3G II 3D Ex ec IIC T4 Gc Ex tc IIIC T135°C Dc 40°C ≤ Ta ≤ +70°C QPS21ATEX7003X </div> <div style="font-size: 2em;">  </div> </div>