

EGF Flame Tracker*

Fast flame supervision for enclosed ground flare pilots

Improved safety

Reuter-Stokes ultraviolet flame sensor constantly monitors the flare pilot, ensuring it is ready for a flare event. Solid state technology provides rapid sensor reaction. The EGF Flame Tracker responds in seconds to changes in the flame. Reuter-Stokes silicon carbide technology is designed for use with multiple fuels and can even tolerate partial mixtures of hydrogen. The flare is key to plant safety and the pilot is key to flare operation. Make sure yours is always ready with EGF Flame Tracker.

Advantages

High reliability

Reuter-Stokes has been performing flame supervision for over 23 years in extremely high temperature and high vibration environments. EGF Flame Trackers are built for high reliability in harsh environments. The sensor is hermetically sealed, ruggedly built, and needs no external cooling. The 4-20 mA current loop output is an industry standard for flame sensing and is robust in the presence of electromagnetic interference (EMI).

Restored confidence

Know right away that your pilot flame is lit. EGF Flame Tracker is an optical UV sensor that responds within seconds. Its low light detection capabilities make it applicable to pilots that are up to 40 feet long. Thermocouples may make you wait a quarter hour and that's too long. Eliminate the guesswork with a sensor that responds immediately.

Easy maintenance

EGF Flame Trackers are simple to install. They are attached to the back end of the pilot opposite the flame where they are easily accessible. Because they are outside the enclosed ground flare, there is no need to pull the entire pilot to install an EGF Flame Tracker. The installation is almost as easy as changing a light bulb!

Performance benefits


- Provides reliable operation when using almost any fuel
- Responds quickly to changes in the pilot flame
- Easy installation outside the enclosed ground flare
- High sensitivity for low light operation

Specifications

Sensor responsivity and hydrocarbon flame emission spectrum.



Spectral response



Flame emission

EGF Flame Tracker response

Peak sensitivity closely matches the key flame peak at 310 nm.

Operating

Power requirements	24 VDC nominal, 12-30 VDC @ 100 mA
Output	4-20 mA
Response time	< 12 seconds
Temperature range	-40°C to +85°C

Material

Body mount	AISI 316 stainless steel
Housing	AISI 304 stainless steel (sealed and Argon filled)
Mechanical interface	3/4" NPT female
Electrical connector	MIL-C-38999 Series III size 15 (5pin)
Sensor	Silicon Carbide (SiC) photodiode

Copyright 2019 Baker Hughes Company. All rights reserved. Baker Hughes provides this information on an “as is” basis for general information purposes. Baker Hughes does not make any representation as to the accuracy or completeness of the information and makes no warranties of any kind, specific, implied or oral, to the fullest extent permissible by law, including those of merchantability and fitness for a particular purpose or use. Baker Hughes hereby disclaims any and all liability for any direct, indirect, consequential or special damages, claims for lost profits, or third party claims arising from the use of the information, whether a claim is asserted in contract, tort, or otherwise. Baker Hughes reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your Baker Hughes representative for the most current information.

GEA13662G (11/2019)



[bakerhughes.com](https://www.bakerhughes.com)